# TM SERIES 3" & 4" WATER METERS



TM Series Meters are designed for use in water applications. The 3" and 4" models are shown here. Choose Spigot (pipe end), NPT or 150# ANSI Flange fittings.

For complete part number, see "Number Reference" chart on page 46.

7.1	ΙВΛ	. •	no/	$\mathbf{D} = \mathbf{A}$	DING
744	11.4		<b>1</b> /0	1.1	

### Features and Benefits:

- Available in Spigot, NPT and Flange fittings.
- Displays in gallons, litres and cubic feet.
- Indicates Batch, Cumulative Totals and Rate of Flow.
- One-piece field replaceable turbine assembly.
- Spigot models may be cut to length.
- Meets Schedule 80 specifications.
- Lithium battery life: 5 years.
- Non-volatile totals means amounts are retained when batteries are replaced or power is lost.

## Applications:

- OEM water treatment equipment / skids
- Sub-metering of facility water usage
- Waste water treatment equipment
- Chemical feed systems
- Cooling towers
- Irrigation

TM SERIES – SPECIFICATIONS							
Design Type:	Turbine						
Fitting Size:	3" 4"						
Fitting Type:	Schedule 80 Spigot (Pipe) End, NPT (Female)						
	or 150# ANSI Flange						
Flow Range:							
3" - TM 300:	40 - 400 GPM (151 - 1514 LPM)						
Extended Range:	30 - 600 GPM (131 - 2271 LPM)						
4" - TM400:	60 - 600 GPM (227 - 2271 LPM) 40 - 800 GPM (151 - 3028 LPM)						
Extended Range:	,						
Accuracy:	± 3.0% of reading						
Pressure Rating:	225 PSIG / 15.3 BAR at 73° F (23° C)						
For CE Applications:	135 PSIG / 9.1 BAR at 73° F (23° C)						
Operating Temperature:	+32° F to +140° F (0° to +60° C)						
Battery Life:	5 Years						
Wetted Materials:							
Housing:	PVC						
Bearings:	PEEK						
Shaft & Thrust Washers:	Stainless Steel						
Rotor & Nose Cone:	Acetal						
Signal Generator:	Ferrite						
Shipping Weight (approx.):	Spigot	NPT	Flange				
3" - TM300:	2.4 lbs.	3.9 lbs.	5.8 lbs.				
411	(1.09 kg)	(1.77 kg)	(2.63 kg)				
4" - TM400:	3.7 lbs.	6.1 lbs.	9.2 lbs.				
	(1.68 kg)	(2.77 kg)	(4.17 kg)				
Display Features:	Rate of Flow, Batch and Cumulative Totals,						
	Field Calibration available						
Pulse Output:	Open Collector (NPN)						

### **ELECTRONIC CHOICES**

GG, GX, GA or SC: See Electronics Section.

#### **APPROVALS**





